

BEST - your custom made sectional garage doors



STANDARD EQUIPMENT:

Galvanized steel guide rails made of 1.5 mm steel sheet

Double horizontal tracks

Powder coated springs quaranted for maximum 50,000 cycles(according to the calculation program)

Insulated steel panels made of 0.5 mm galvanized steel sheets, CFC polyurethane, total thickness of 42mm

Reinforcement(45 mm) for panels at the top and the bottom for the whole length.

Panels model MULTI, texture WOOD-GRAIN/ STUCCO: STANDARD COLORS = RAL 9002 / RAL 8019 / RAL 9006 / RAL 3000 / RAL 5010 / RAL 7016 / RAL 6005 / RAL 6009

Panels of 42 mm thickness, Panels with FINGER SAFE SYSTEM

End-caps(metallic), STUCCO design, painted in WHITE = RAL 9002

Black ALU profile of 40x 40mm for the upper and lower panel

Your PERSONAL DISCOUNT have to be applied to this price list !!

Shaft with coupler

Lower seal(residential type gasket), for the lower panel

Upper seal(gasket) to be fastened on the black aluminun profile

PTFE rolls with bearings

Lateral supports for rolls and and intermediate hinges with 2 mm thickness

Installation perforated corner 1 bar = 3 m / "L" type fixing supports, L = 750 mm 1 pair = 2 pieces

*Width = installation width/Height= installation height

* SYSTEM LHF (springs on the beam)requires a MINIMUM HEADROOM of=210 mm(manual)/250 mm(electric)

H/L	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3400	3500	3600	3700	3800	3900
1865	471	480	490	502	565	574	587	593	605	615	624	633	643	652	665	674	683	696	705	714
2000	505	518	527	540	602	615	624	636	646	655	668	677	690	699	711	724	733	746	755	768
2120	521	534	546	558	624	633	646	655	668	677	690	699	711	724	736	749	758	771	783	796
2240	540	552	565	587	643	655	665	677	690	699	711	724	736	749	761	774	786	799	811	824
2360	558	580	593	605	661	671	686	699	711	724	736	749	761	774	786	799	811	824	836	849
2480	593	605	618	630	686	696	711	724	736	749	761	777	789	802	817	830	842	858	870	883
2495	615	630	643	655	711	721	736	749	761	777	789	802	817	830	842	858	870	886	899	914
2615	636	652	665	680	733	746	761	774	789	802	817	830	846	858	874	886	902	917	955	967
2735	649	665	677	711	749	761	777	792	805	821	833	849	864	880	892	908	945	961	977	992
2855	671	686	721	733	771	786	802	817	833	846	861	877	892	908	924	961	977	992	1008	1023
2975	683	718	733	758	786	802	817	833	849	864	877	892	911	952	967	983	998	1014	1030	1045
3000	696	730	746	783	802	814	833	849	864	880	895	911	930	970	989	1005	1020	1036	1051	1070


*Width = installation width/Height= installation height

H/L	4000	4100	4200	4300	4400	4500	4600	4700	4800	4900	5000	5100	5200	5300	5400	5500	5600	5700	5800	5900	6000
1865	727	736	746	758	768	780	789	802	811	824	833	846	858	886	895	908	917	927	939	948	1033
2000	777	789	802	814	827	836	849	858	870	883	914	927	939	948	961	970	983	995	1008	1017	1104
2120	805	817	833	842	855	867	880	911	924	936	948	961	973	983	995	1008	1020	1033	1042	1058	1142
2240	836	849	861	874	908	920	933	945	958	970	980	995	1008	1020	1033	1045	1058	1070	1114	1126	1182
2360	861	877	914	924	936	948	964	977	989	1002	1014	1030	1042	1055	1067	1114	1126	1139	1148	1161	1214
2480	920	933	945	961	973	986	1002	1014	1026	1039	1055	1101	1114	1126	1142	1154	1167	1179	1195	1207	1264
2495	948	964	977	989	1005	1020	1033	1045	1061	1073	1089	1136	1148	1161	1176	1189	1201	1217	1232	1245	1298
2615	983	998	1011	1023	1039	1055	1067	1083	1098	1145	1158	1173	1189	1201	1217	1229	1242	1260	1273	1289	1342
2735	1005	1020	1036	1048	1064	1114	1129	1145	1158	1170	1189	1201	1217	1232	1245	1260	1310	1326	1338	1354	1373
2855	1039	1051	1067	1083	1101	1151	1164	1179	1195	1211	1226	1242	1254	1273	1285	1304	1351	1367	1382	1398	1420
2975	1061	1076	1129	1145	1161	1176	1192	1207	1223	1239	1254	1270	1323	1338	1351	1370	1382	1401	1413	1432	1454
3000	1086	1101	1154	1170	1189	1201	1217	1232	1251	1267	1282	1301	1354	1367	1382	1398	1416	1432	1448	1466	1488

*dimensions from table are for offer purposes, the doors can be manufactured at any intermediate measure

**for doors with L > 5500mm panels have double endcaps + 2 lateral supports for rolls

BEST- PANELS TYPE AND COLORS

Panel Color	Panel Texture	    				
		Multi	Single	Flat	With blocks	Multi Rib
White (RAL 9002)	Woodgrain	standard	* standard	standard	+2 euro/mp	
	Stucco	standard	* standard	standard	+2 euro/mp	
	Smooth	+3 euro/mp	* +3 euro/mp	+3 euro/mp		+3 euro/mp
	Perfect touch					
Brown (Ral 8019)	Woodgrain	standard	* standard	standard	+2 euro/mp	
	Stucco	standard	* standard	standard	+2 euro/mp	
	Smooth	+3 euro/mp	* +3 euro/mp	+3 euro/mp		+3 euro/mp
	Perfect touch					
Silver (Ral 9006)	Woodgrain					
	Stucco	standard		standard	+2 euro/mp	
	Smooth	+3 euro/mp		+3 euro/mp		+3 euro/mp
	Perfect touch					
Anthracite (Ral 7016)	Woodgrain					
	Stucco	standard		standard		
	Smooth	+3 euro/mp	* +3 euro/mp	+3 euro/mp		+3 euro/mp
	Perfect touch					
Blue (Ral 5010)	Woodgrain					
	Stucco	standard				
	Smooth					
	Perfect touch					
Red (Ral 3000)	Woodgrain					
	Stucco	standard				
	Smooth					
	Perfect touch					
Light green (Ral 6005)	Woodgrain	standard	* standard	standard	+2 euro/mp	
	Stucco	standard	* standard	standard		
	Smooth	+3 euro/mp	* +3 euro/mp	+3 euro/mp		+3 euro/mp
	Perfect touch					
Dark green (Ral 6009)	Woodgrain		* standard			
	Stucco		* standard			
	Smooth		* +3 euro/mp			+3 euro/mp
	Perfect touch					
Golden Oak	Woodgrain					
	Stucco					
	Smooth					
	Perfect touch	+25 euro/mp	+25 euro/mp	+25 euro/mp	+27 euro/mp	
Walnut	Woodgrain					
	Stucco					
	Smooth					
	Perfect touch	+25 euro/mp	+25 euro/mp	+25 euro/mp	+27 euro/mp	
Light Oak	Woodgrain					
	Stucco					
	Smooth					
	Perfect touch	+25 euro/mp	+25 euro/mp	+25 euro/mp	+27 euro/mp	
Mahagony	Woodgrain					
	Stucco					
	Smooth					
	Perfect touch	+25 euro/mp	+25 euro/mp	+25 euro/mp	+27 euro/mp	
Wenge	Woodgrain					
	Stucco					
	Smooth					
	Perfect touch	+25 euro/mp	+25 euro/mp	+25 euro/mp		

* WARNING: 615mm panels do not have line on the middle. The line is up or down.

 On stock - standard delivery term

 By order delivery term 5-6 weeks

BEST-ACCESSORIES and ADDITIONAL OPTIONS for doors



Description		U.M.	Price
Painting in RAL colors (on the exterior part of the panels)		mp	28
LHR sliding system, minimum beam = 75mm (manual) / 115mm (electric)		Set	106
SAFETY SYSTEMS	Safety system against springs break- down	pair	26
	Safety system against cables break-down (LHF)	pair	41
	Safety system against cables break-down (LHR)	pair	22
WINDOWS INSERTIONS GRILLES	Rectangular window 525x350mm with black PVC frame	Pc.	44
	Rectangular window 525x350mm with black PVC frame - CROSS Model	Pc.	50
	Rectangular window 700x370mm with black PVC frame	Pc.	56
	Rectangular window 607x176mm with black PVC frame	Pc.	75
	Round window Ø330mm with black PVC frame	Pc.	97
	Square window Ø 310mm with Stainless Steel frame	Pc.	144
	Round window Ø330mm with black PVC frame	Pc.	222
	Stainless Steel Insertion on panel - rectangular shape 220mm	Pc.	44
	Stainless Steel Insertion on panel - round Ø280mm shape	Pc.	69
	Ventilation grilles 480x98	Pc.	22
GLAZED PANELS	Glazed aluminium panel model GLAZED, Lmax = 4000mm (2 sheets of 2 mm plexiglass),RAL colors : White (RAL 9002), Brown (RAL 8019), Anthracite (RAL 7016), Anodized aluminum	m /sect	60
	Glazed aluminium panel model GLAZED, Lmax = 5320mm (2 sheets of 2 mm plexiglass),RAL colors : White (RAL 9002), Brown (RAL 8019), Anthracite (RAL 7016), Anodized aluminum(standard equipped with L profile for reinforcement)	m /sect	69
	Glazed aluminium panel model GLAZED, Lmax = 7000mm (2 sheets of 2 mm plexiglass),RAL colors : White (RAL 9002), Brown (RAL 8019), Anthracite (RAL 7016), Anodized aluminum(mandatory with omega profile for glazed panels)	m /sect	60
	Aluminum OMEGA profile for reinforcement of the glazed panels	m	22
	Glazed aluminium panel model FULL GLAZED, Lmax = 3100mm (1 sheet of 4mm plexiglass),RAL colors : White (RAL 9002), Brown (RAL 8019), Anthracite (RAL 7016), Anodized aluminum (ATTENTION - you cannot insert a wicket door)	m /sect	48
	Glazed aluminium panel model FULL GLAZED, Lmax = 5000mm (1 sheet of 4mm plexiglass),RAL colors : White (RAL 9002), Brown (RAL 8019), Anthracite (RAL 7016), Anodized aluminum (ATTENTION - you cannot insert a wicket door)	m /sect	48
	Aluminum profile of glazed panels - Painting in RAL colors	m /sect	21
WICKET DOORS	Wicket door with threshold, door closer INCLUDED¹, RAL colors - On STOCK: White (RAL 9002), Brown (RAL 8019), Anthracite (RAL7016), Blue (RAL5010), Red (Ral3000) si Anodized aluminum - By ORDER 5-6 delivery term: Black (RAL 9005), Light green (RAL 6005), Dark green (RAL 6009)	Pc.	670
	Wicket door without threshold, door closer INCLUDED¹, RAL colors - On STOCK: White (RAL 9002), Brown (RAL 8019), Anthracite (RAL7016), Blue (RAL5010), Red (Ral3000) si Anodized aluminum - By ORDER 5-6 delivery term: Black (RAL 9005), Light green (RAL 6005), Dark green (RAL 6009)	Pc.	830
	Wicket door profiles painting in other RAL colors	Pc.	47
	Wicket door with threshold, door closer INCLUDED¹, wood imitations - BY ORDER 5-6 weeks: Light Oak, Golden Oak, Walnut, Mahagony, Green wood	Pc.	934
	Wicket door without threshold, door closer INCLUDED¹, wood imitations - BY ORDER 5-6 weeks: Light Oak, Golden Oak, Walnut, Mahagony, Green wood	Pc.	1094
	Anti-panic bar for wicket door	Set	275

BEST-ACCESSORIES and ADDITIONAL OPTIONS for doors



ANNEXED WICKET DOORS	Annexed wicket door without door closer, RAL colors - On STOCK: White (RAL 9002), Brown (RAL 8019), Anthracite (RAL7016), Blue (RAL5010), Red (Ral3000) si Anodized aluminum - By ORDER 5-6 delivery term: Black (RAL 9005), Light green (RAL 6005), Dark green (RAL 6009)	buc	766
	RAL painting of annexed wicket door profile	buc	47
	Annexed wicket door, without door closer, wood-imitation colors - BY ORDER 5-6 weeks: Light Oak, Golden Oak, Walnut, Mahagony, Green wood	buc	818
	Door closer with guide rail for annexed wicket door	buc	75
PROFILES	OMEGA profile for panels reinforcement - mandatory for panels 1 and 4, doors with wicket door included, width L > 4000 mm - mandatory for all the panels, doors with wicket door included, width L > 5250mm - mandatory 2 profiles on each panel, doors with wicket door included, width L > 6000mm	m	6
	Aluminum lower profile 100 mm for reinforcement - mandatory for doors with wicket door inserted, door width 5000mm<L<6000mm	m	25
	System(profile + PVC endcaps) for closing the horizontal tracks	m	6
HANDLES and LOCKS	Handle(recessed)	Pc.	11
	Handle (applied on surface)	Pc.	7
	Bolt(hand bolt)	Pc.	10
	Industrial lock (for manual operation)	Pc.	48
	Residential lock (for manual operation)	Pc.	154
	ECO residential lock(lock with cables for manual operation, L max = 5000mm)	Pc.	37
GASKETS	Lower seal from EPDM with tubular structure - industrial gasket	m	3
	Upper seal - to be installed on the beam (L=5060mm)	Pc.	3
FIXING SYSTEMS	Fixing support for horizontal tracks, L profiles , 2 pieces	Set	12
	Perforated corner (profile at 3m) for installation	Pc.	12
PVC stopper for manually operated door		Set	5
Packing of panels in carton boxes - price per door		Pc.	28
RECTANGULAR PROFILES	Rectangular profile, galvanized, 100x50x2mm (profile at 6m)	Pc.	54
	Rectangular profile, galvanized, 50x50x2mm (profile at 6m)	Pc.	42
	Electrostatic painting for rectangular profile(profile at 6m)	Pc.	66
	PVC foiling for rectangular profile in wood -imitation colors (profile at 6m)	Pc.	236

- 1. Wicket door in full panels, laterall position for door with Lmax = 4500mm
- 1. Wicket door in full panels , central position for door with L max = 6000mm
- 1. Wicket door in glazed panels, laterall position for doors with Lmax = 4500mm
- 1. Wicket door in glazed panels, central position for door with Lmax = 5000mm

BEST- Drive units + ADDITIONAL OPTIONS in automatic door.



The drive should be chosen depending on the size of the door, rail- depending the height of the door.

The drive and the rail constitute one unit set and cannot be order separately.

Description	U.M.	Price
Electric drive BFT ITALY : TIZIANO 600 N engine(tractive force 60 Kg), 24V supply,electronic limiters, speed of 5m/min, can be unlock to manual, intensive use, possibility to connect: remote controls(maximum 10 Pieces), photocells, temperature range: - 20°C - + 60°C.Maximum Hdoor: 2850mm. Kit include remote controls: MITTO 2 (2 pieces)	Pc.	198
Electric drive BFT ITALY : BOTTICELI 800 N engine(tractive force 80 Kg), 24V supply,electronic limiters, speed of 5m/min, can be unlock to manual, intensive use, possibility to connect: remote controls(maximum 60 Pieces), photocells, temperature range: - 20°C - + 60°C.Maximum Hdoor: 2850mm. Kit include remote controls: MITTO 2 (2 pieces)	Pc.	284
Electric drive BFT ITALY : EOS 1200 N engine(tractive force 120 Kg), 24V supply,electronic limiters, speed of 5m/min, can be unlock to manual, intensive use, possibility to connect: remote controls(maximum 60 Pieces), photocells, temperature range: - 20°C - + 60°C.Maximum Hdoor: 2850mm. Kit include remote controls: MITTO 2 (2 pieces)	Pc.	349
Electric drive BFT ITALY: ARGO 55 Nm engine , 1 x 230 V supply, incorporated radio receiver, manual release with cord, suitable for doors with maximum 20 sqm surface	Pc.	520
Universal radio receiver - CLONIX 2E	Pc.	72
Remote control MITTO2 12 V - B2	Pc.	23
Remote control MITTO2 12 V- B4	Pc.	29
Emergency unlock of the engine(from the outside , only if there is no other access)	Pc.	43
Wireless button with 4 channels -RB	Pc.	51
Photocells for BFT engines-DESME A15	Pc.	55
Rail extension - PBE(only for Botticelli/Eos engines)	Pc.	45
Lamp 24V- RADIUS B LTA 24 R2	Pc.	54
Selector with key - Q.BO WM KEY	Pc.	28
Selector with wireless code- Q.BO TOUCH	Pc.	113

Price List available from **15.03.2016**

Prices are in Euro and have TRANSPORT to BG INCLUDED .

This Price List cancel ALL the PREVIOUS PRICE LISTS.